

HIGH-AMP CIRCUIT BREAKER

GCA SERIES, GCA-A SERIES, GCA-B SERIES

RoHS

WATERPROOF (MEET IP67)
Surface Mount

Applications :

Typically used in auxiliary and accessory circuits-trucks, buses, RV's and marine applications

Others might include battery chargers and DC audio systems.

Specifications :

- Ratings: 25A to 200A
- Voltage: 42 VDC Maximum
- Interrupt Rating: 3000 A @ 30VDC.
- Operating Temperature: -32°C to 82°C
- Storage Temperature: -34°C to 149°C
- Standard Testing: SAE J1625; SAE J1171 (Ignition Protected)
- Housing: Thermoset Plastic, UL rated 94VO
- Approval:  50A-150A 32VDC

Ordering Information

Part Number	Ampere (A)	Part Number	Ampere (A)	Part Number	Ampere (A)
GCA-25	25 A	GCA-70	70 A	GCA-135	135 A
GCA-30	30 A	GCA-80	80 A	GCA-140	140 A
GCA-40	40 A	GCA-90	90 A	GCA-150	150 A
GCA-50	50 A	GCA-100	100 A	GCA-180	180 A
GCA-60	60 A	GCA-120	120 A	GCA-200	200 A
GCA-180, GCA-200 has a patent					

PART NO. : GCA series
Manual Switch Reset, Type III



Ordering Information

Part Number	Ampere (A)	Part Number	Ampere (A)	Part Number	Ampere (A)
GCA-A25	25 A	GCA-A70	70 A	GCA-A135	135 A
GCA-A30	30 A	GCA-A80	80 A	GCA-A140	140 A
GCA-A40	40 A	GCA-A90	90 A	GCA-A150	150 A
GCA-A50	50 A	GCA-A100	100 A	GCA-A180	180 A
GCA-A60	60 A	GCA-A120	120 A	GCA-A200	200 A
GCA-A180, GCA-A200 has a patent					

PART NO. : GCA-A series
Manual Reset, Type III



Ordering Information

Part Number	Ampere (A)	Part Number	Ampere (A)	Part Number	Ampere (A)
GCA-B25	25 A	GCA-B70	70 A	GCA-B135	135 A
GCA-B30	30 A	GCA-B80	80 A	GCA-B140	140 A
GCA-B40	40 A	GCA-B90	90 A	GCA-B150	150 A
GCA-B50	50 A	GCA-B100	100 A	GCA-B180	180 A
GCA-B60	60 A	GCA-B120	120 A	GCA-B200	200 A

PART NO. : GCA-B series
Automatic Reset, Type I

